

Agri-Vac

7614



WALINGA
INC.

TOUGH TO BEAT IN THE LONG RUN

WALINGA.COM.AU



7614

SPECIFICATIONS FOR: Walinga Pneumatic Grain Moving Unit Model 7614

	7614 DLX
HEIGHT	244 cm
WIDTH	234 cm
LENGTH	272 cm
WEIGHT	1498 kg
DISCHARGE HEIGHT	5.0m maximum
HP REQUIRED	130 - 150 hp
PTO SPEED	1000 RPM
LINE SIZE	7" maximum
TIRES	Two standard farm implement
WHEELS	15", 5 stud
BLOWER	#614 Walinga SRT (Sound Reduction Type), CORVOR™ Hard Coating, Positive Displacement Blower
AIRLOCK	#2018 cast iron shell, precision machined housing, 10 vane rotor Hardox steel tips, hydraulically driven, reversible rotation
DRIVE	Tongue mounted drive shaft with V-type 5 roove sheaves & belts
HYDRAULICS	Self Contained
RECEIVER	24" dia. two piece, dual inlets
PRECLEANER	20" dia.
SAFETY	Vacuum/Pressure relief valves

AVAILABLE OPTIONS

- Additional Hose
- Bleed-in valve to reduce hose size
- Electric or diesel power pack
- CORVOR™ Hard Coated Airlock
- 540 RPM PTO Speed

STANDARD ACCESSORIES

- Hose carrier
- Dust Precleaner to reduce wear
- Walinga SRT (Sound Reduction Type) Positive Displacement CORVOR™ Hard Coated Blower
- 6" clean-up hose package
- Hydraulic truck loading kit with cyclone
- Two 7" dia. x 12' stainless steel delivery lines
- One 6" dia. suction nozzle
- One 6" dia. x 12' flexible clean-up hose with swivel coupling
- One 6" dia. suction floor sweep with wheels
- One 7" to 6" adaptor
- Rhino Liner covering high wear areas in receiver tank and boom cyclone

The WALINGA 7614 Agrivac is the ultimate in versatility when it comes to tricky grain transfer operations. Quick enough to load transport at up to 100 tonnes per hour yet flexible enough to fit in tight loading spaces.

Moving grain with air ensures gentle handling of all types of grain maintaining seed quality. The flexible arrangement of suction and/or delivery piping allows operation in many areas where tradition augers or conveyors cannot operate.



1800 242 699

customvac.com.au

Suction Nozzle



Floor Sweep Nozzle



7614 DLX REAR VIEW

Due to continuous product development, specifications are subject to change without notice. Some items shown may be optional.
*Capacities based on using 12' (3.65 m) suction line and truck loading kit. Capacity will vary with condition of product.

Head Office

R.R. #5,
Guelph, Ontario
Canada N1H 6J2
Tel: 519.824.8520
Tel: 888.925.4642
Fax: 519.824.5651

Michigan

1190 Electric Ave.
Wayland, Michigan
USA 49348
Tel: 616.877.3470
Tel: 800.466.1197
Fax: 616.877.3474

Manitoba

70 3rd Ave. N.E.
Box 1790
Carman, Manitoba
Canada R0G 0J0
Tel: 204.745.2951
Fax: 204.745.6309

Ontario

938 Glengarry Cres.
Fergus, Ontario
Canada N1M 2W6
Tel: 519.787.VACS (8227)
Fax: 519.787.8210

Australia

Customvac Australia
24 Molloy St.
Toowoomba Qld 4350
Australia
Tel: 1800 242 699

